

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. ~~An electronic circuit~~circuit, comprising:

 a first transistor that becomes on-state when a scan line is selected;

 a capacitive element ~~for holding~~that holds an electrical-charge amount according to a data signal transmitted from a data line via the first transistor; and

 a second transistor whose conduction state is controlled, based on the electrical-charge amount held in the capacitive element, the second transistor ~~being used for~~ transmitting a current amount corresponding to ~~the~~a conduction state to an electronic element,

 ~~wherein~~ the electrical-charge amount according to the data signal ~~can be~~being accumulated in the capacitive element even when either a two-level-data voltage or a multilevel-data voltage is transmitted as the data signal.
2. ~~An~~The electronic circuit according to Claim 1,

 ~~wherein~~ the two-level-data voltage and the multilevel-data voltage ~~are~~being transmitted via ~~one and the same~~ first switching transistor.
3. ~~An~~The electronic circuit according to Claim 1, further comprising:

 a third transistor ~~for resetting~~that resets the electrical-charge amount held in the capacitive element.
4. ~~An~~The electronic circuit according to Claim 1, further comprising:

 a fourth transistor of which a conductivity is controlled according to the multilevel-data voltage, the fourth transistor being connected between ~~the~~a gate and a drain of the second transistor, the fourth transistor ~~being used for~~ compensating ~~the~~a threshold voltage of the second transistor.

5. ~~An~~The electronic circuit according to Claim 1, further comprising:
a fifth transistor that determines the timing of driving the electronic element.
6. ~~An~~The electronic circuit according to Claim 1, ~~wherein~~ the electronic element ~~is being~~ an EL element.
7. ~~An~~The electronic circuit according to Claim 6, ~~wherein~~ the EL element ~~has~~ having a light-emission layer formed of an organic material.
8. An electro-optical ~~device~~device, comprising:
a plurality of scan lines;
a plurality of data lines;
a plurality of unit circuits;
a first data-voltage output circuit ~~for outputting~~that outputs a two-level-data voltage as a data signal to each of the plurality of unit circuits via a respective data line of the plurality of data lines;
a second data-voltage output circuit ~~for outputting~~that outputs a multilevel-data voltage to each of the plurality of unit circuits via a respective data line of the plurality of data lines.
9. An electro-optical device according to Claim 8,
~~wherein~~ the two-level-data voltage and the multilevel-data voltage ~~are being~~ transmitted via one and the same data line of the plurality of data lines.
10. An electro-optical device according to Claim 8,
~~wherein~~ the two-level-data voltage and the multilevel-data voltage ~~are being~~ transmitted via data lines of the plurality of data lines that are different from each other.
11. An electro-optical ~~device~~device, comprising:
a plurality of scan lines;
a plurality of data lines provided so as to cross the scan lines;

a unit circuit that is provided so as to correspond to each of the intersections of the plurality of scan lines and the plurality of data lines and that transmits a drive current according to a data voltage transmitted via a respective data line of the plurality of data lines to an electro-optical element; and

~~a control means for generating and outputting~~ device that generates and outputs either a two-level-data voltage for applying digital-gray-scale modulation to the electro-optical element or a multilevel-data voltage for applying analog-gray-scale modulation to the electro-optical element, based on image data.

12. ~~An~~ The electro-optical device according to Claim 11,

~~wherein the unit circuit comprises~~ comprising:

a first transistor that becomes on-state when a respective scan line of the plurality of scan lines is selected;

a capacitive element ~~for holding~~ that holds either a two-level-data voltage for digital-gray-scale modulation or a multilevel-data voltage for analog-gray-scale modulation transmitted from a respective data line of the plurality of data lines via the first transistor as an electrical-charge amount; and

a second transistor whose conduction state is controlled, based on the electrical-charge amount held in the capacitive element, the second transistor ~~being used for~~ transmitting a current amount corresponding to the conduction state to the electro-optical element.

13. ~~An~~ The electro-optical device according to Claim 12,

~~wherein the unit circuit further comprises~~ comprising:

a third transistor ~~for resetting~~ that resets the electrical-charge amount held in the capacitive element.

14. ~~An~~ The electro-optical device according to Claim 12,

~~wherein~~ the unit circuit further ~~comprises~~ comprising a fourth transistor ~~for compensating that compensates the~~ a threshold voltage of the second transistor, the fourth transistor being connected between ~~the~~ a gate and a drain of the second transistor when the analog-gray-scale modulation is performed.

15. ~~An~~ The electro-optical device according to Claim 11,
~~wherein~~ the unit circuit further ~~comprises~~ comprising a fifth transistor ~~for determining that determines~~ the timing of driving the electro-optical element.

16. An electro-optical device according to Claim 11,
~~wherein~~ the electro-optical element ~~is~~ being an EL element.

17. An electro-optical device according to Claim 16,
~~wherein~~ the EL element ~~has~~ having a light-emission layer formed of an organic material.

18. ~~An~~ The electro-optical device according to Claim 11,
~~wherein~~ the control ~~means~~ generates device generating the two-level-data voltage for applying the digital-gray-scale modulation to the electro-optical element in low-electrical-power-consumption mode and the multilevel-data voltage for applying the analog-gray-scale modulation to the electro-optical element in non-low-electrical-power-consumption mode ~~for driving that drives~~ the electro-optical element.

19. ~~An~~ The electro-optical device according to Claim 11,
~~wherein~~ the control ~~means~~ generates device generating the two-level-data voltage for applying the digital-gray-scale modulation to the electro-optical element when the image data is first display data and the multilevel-data voltage for applying the analog-gray-scale modulation to the electro-optical element when the image data is second display data whose display quality is higher than that of the first display data ~~for driving that drives~~ the electro-optical element.

20. ~~An~~ The electro-optical device according to Claim 18,
~~wherein the control means comprises~~ device comprising:
a two-level-data-voltage generation circuit ~~for generating~~ that generates the two-level-data voltage for applying the digital-gray-scale modulation to the electro-optical element; and

a multilevel-data-voltage generation circuit ~~for generating~~ that generates the multilevel-data voltage for applying the analog-gray-scale modulation to the electro-optical element.

21. An electro-optical device according to Claim 18, ~~wherein~~:
the device ~~comprises~~ comprising, between the control ~~means~~ device and each of the data ~~line~~ lines, a first output circuit ~~for outputting~~ that outputs the two-level-data voltage transmitted from the two-level-data-voltage generation circuit and a second output circuit ~~for outputting~~ that outputs the multilevel-data voltage transmitted from the multilevel-data-voltage generation circuit; and further ~~comprises~~ comprising a switching circuit ~~for outputting~~ that outputs either the two-level-data voltage from the first output circuit or the multilevel-data voltage from the second output circuit to the data line.

22. ~~An~~ The electro-optical device according to Claim 11,
~~wherein the digital-gray-scale modulation is~~ being time-ratio gray-scale modulation.

23. ~~An~~ The electro-optical device according to Claim 22,
~~wherein the time-ratio gray-scale modulation is~~ being performed by writing the two-level-data voltage into the unit circuit corresponding to one of the scan lines selected in sequence and starting transmission of a current with a level according the two-level-data voltage to the electro-optical element at the same instant, and stopping the current transmission to the electro-optical element after a predetermined time.

24. A method for driving an electro-optical ~~device~~ device, comprising:
a plurality of scan lines;
a plurality of data lines provided so as to cross the scan lines; and
a unit circuit that is provided so as to correspond to each of ~~the~~ intersections of the scan lines and the data lines and that transmits a drive current according to a data voltage transmitted via a respective data line of the plurality of data lines to an electro-optical element,

~~wherein~~ the electro-optical element is being driven by generating a two-level-data voltage for applying digital-gray-scale modulation to the electro-optical element in low-electrical-power-consumption mode and a multilevel-data voltage for applying analog-gray-scale modulation to the electro-optical element in non-low-electrical-power-consumption mode.

25. A method for driving an electro-optical ~~device~~ device, comprising:
a plurality of scan lines;
a plurality of data lines provided so as to cross the scan lines; and
a unit circuit that is provided so as to correspond to each of ~~the~~ intersections of the scan lines and the data lines and that transmits a drive current according to a data voltage transmitted via a respective data line of the plurality of data lines to an electro-optical element,

~~wherein~~ the electro-optical element is being driven by generating a two-level-data voltage for applying digital-gray-scale modulation to the electro-optical element when image data is first display data and a multilevel-data voltage for applying analog-gray-scale modulation to the electro-optical element when the image data is second display data whose display quality is higher than that of the first display data.

26. A The method for driving an electro-optical device according to Claim 24,

~~wherein~~ the digital-gray-scale modulation ~~is~~ being time-ratio gray-scale modulation.

27. ~~A~~ The method for driving an electro-optical device according to Claim 26, ~~wherein~~ the time-ratio gray-scale modulation ~~is~~ being performed by writing the two-level-data voltage into the unit circuit corresponding to one of the scan lines selected in sequence and starting transmission of a current with a level according the two-level-data voltage to the electro-optical element at the same instant, and stopping the current transmission to the electro-optical element after a predetermined time.

28. An electronic apparatus having ~~an~~ the electro-optical device according to Claim 8 mounted thereon.